PÉGAS® · SWISS SAW BLADES · SINCE 1966

Usage guide & technical data

Pégas® scroll saw blades

This guide helps everyone, from beginner to expert, to pinpoint the ideal blade for their project, based on the type of material [1], its thickness [2], the style of cut to make [3], the expected finish [4], the hole to drill for inside cuts [5] or the kerf required.

Scroll saw blades made in Switzerland

THE RANGE

	STANDARD	*PINNED*
SKIP		
SUPER-SKIP		—
DOUBLE SKIP		—
MGT		—
SKIP REVERSE		
DOUBLE SKIP REVERSE		—
SUPER-HOOK		—
SPIRAL		—
METAL CUTTING		—
REGULAR		
HOOK	—	
SKIP PROGRESSIVE		—
REGULAR PROGRESSIVE		—
DOVETAIL		—

TECHNICAL DATA BY PRODUCT

[1] material type · [2] material thickness · [3] cutting radius · [4] finish quality · [5] gauge

Suitability by material : ✓ Recommended ~ Possible – Not recommended

							[1] Material type							[2]	[3] Cutting radius			[4] Finish quality		[5]
Model / art. no.	Univ. no.	Length [in]	Blade thick. [in]	Blade width [in]	TPI	Kerf [in]	Hardwoods	Medium-hard woods	Softwoods	Plywood	Corian & plastics	Non-ferrous metals	Ferrous metals	Recomm. material thick. [in]	Wide	Tight	Very tight	Cut quality	Underside quality	Gauge
Pégas SKIP The all-rounder: from intricate patterns to fast cut-offs.																				
A universal scroll-saw blade, excellent in hard and medium-hard woods. The broad Skip range handles everything from intricate fretwork to fast cut-offs. It works fast and leaves a clean, fine surface.																				
STANDARD																				
90.400	2/0	5.12	0.009	0.024	28.2	0.009	✓	✓	~	~	–	–	–	0.079–0.197	■	■	■	★★★	★★☆	70
90.401	0	5.12	0.009	0.029	25.4	0.010	✓	✓	~	~	–	–	–	0.098–0.236	■	■	■	★★★	★★☆	67
90.402	1	5.12	0.01	0.03	22.6	0.011	✓	✓	~	~	–	–	–	0.118–0.315	■	■	■	★★★	★★☆	64
90.403	2	5.12	0.012	0.031	21.1	0.013	✓	✓	~	~	–	–	–	0.138–0.315	■	■	■	★★★	★★☆	64
90.404	3	5.12	0.013	0.033	19.6	0.014	✓	✓	~	~	–	–	–	0.138–0.394	■	■	■	★★★	★★☆	60
90.405	4	5.12	0.013	0.037	18	0.015	✓	✓	~	~	–	–	–	0.157–0.472	■	■	□	★★★	★★☆	56
90.406	5	5.12	0.014	0.04	17	0.016	✓	✓	~	~	–	–	–	0.177–0.512	■	■	□	★★★	★★☆	55
90.407	6	5.12	0.015	0.044	16	0.017	✓	✓	~	~	–	–	–	0.197–0.591	■	■	□	★★★	★★☆	55
90.408	7	5.12	0.016	0.049	15	0.018	✓	✓	~	~	–	–	–	0.236–0.709	■	■	□	★★★	★★☆	53
90.409	8	5.12	0.017	0.05	14.2	0.019	✓	✓	~	~	–	–	–	0.256–0.787	■	□	□	★★★	★★☆	53
90.410	9	5.12	0.017	0.051	13.5	0.019	✓	✓	~	~	–	–	–	0.276–0.984	■	□	□	★★★	★★☆	52
90.411	10	5.12	0.018	0.054	12.7	0.020	✓	✓	~	~	–	–	–	0.295–1.181	■	□	□	★★★	★★☆	52
90.412	11	5.12	0.019	0.057	12.2	0.021	✓	✓	~	~	–	–	–	0.394–1.575	■	□	□	★★★	★★☆	46
90.413	12	5.12	0.02	0.061	11.4	0.022	✓	✓	~	~	–	–	–	0.472–1.969	■	□	□	★★★	★★☆	46
PINNED																				
90.480	9TPI	5.00	0.02	0.118	9.1	0.028	✓	✓	~	~	–	–	–	0.315–1.969	■	□	□	★★☆	★★☆	12
90.481	18TPI	5.00	0.01	0.079	18	0.014	✓	✓	~	✓	~	–	–	0.157–1.181	■	■	□	★★☆	★★☆	12
90.490	18TPI	2.95	0.015	0.079	18	0.020	✓	✓	~	✓	~	–	–	0.157–0.787	■	■	□	★★☆	★★☆	12
90.491	15TPI	2.95	0.015	0.118	15	0.021	✓	✓	~	✓	~	–	–	0.197–0.984	■	■	□	★★☆	★★☆	12
PINNED · COPING																				
90.550	18TPI	6.50	0.02	0.094	18	0.028	~	✓	✓	~	–	–	–	0.157–1.575	■	□	□	★★☆	★★☆	12

Pégas SUPER-SKIP — Ultra-fast cutting, with no compromise on finish.

The Super-Skip is an ultra-fast blade, with far higher output than the standard Skip. The wider gap between the teeth improves sawdust clearance, while its precise, tooth-by-tooth set makes it as smooth and manoeuvrable as it is powerful.

Model / art. no.	Univ. no.	Length [in]	Blade thick. [in]	Blade width [in]	TPI	Kerf [in]	[1] Material type: Hardwoods	Medium-hard woods	Softwoods	Plywood	Corian & plastics	Non-ferrous metals	Ferrous metals	[2] Recomm. material thick. [in]	[3] Cutting radius: Wide	Tight	Very tight	[4] Finish quality: Cut quality	Underside quality	[5] Gauge
90.579	2/0	5.12	0.009	0.024	21.1	0.010	✓	✓	~	–	✓	–	–	0.059–0.236	■	■	■	★★★	★★☆	70
90.580	0	5.12	0.009	0.029	19	0.011	✓	✓	~	–	✓	–	–	0.079–0.236	■	■	■	★★★	★★☆	67
90.581	1	5.12	0.01	0.03	17	0.011	✓	✓	~	–	✓	–	–	0.098–0.315	■	■	■	★★★	★★☆	64
90.582	2	5.12	0.012	0.031	16	0.013	✓	✓	~	–	✓	–	–	0.118–0.394	■	■	■	★★★	★★☆	64
90.583	3	5.12	0.013	0.033	14.7	0.014	✓	✓	~	–	✓	–	–	0.157–0.394	■	■	■	★★★	★★☆	60
90.584	4	5.12	0.013	0.037	13.7	0.015	✓	✓	~	–	✓	–	–	0.197–0.472	■	■	□	★★★	★★☆	56
90.585	5	5.12	0.014	0.04	12.7	0.016	✓	✓	~	–	✓	–	–	0.315–0.591	■	■	□	★★★	★★☆	55
90.586	6	5.12	0.015	0.044	11.9	0.017	✓	✓	~	–	✓	–	–	0.315–0.709	■	■	□	★★★	★★☆	55
90.587	7	5.12	0.016	0.049	11.2	0.018	✓	✓	~	–	✓	–	–	0.394–0.787	■	■	□	★★★	★★☆	53
90.588	8	5.12	0.017	0.05	10.7	0.019	✓	✓	~	–	✓	–	–	0.472–0.787	■	□	□	★★★	★★☆	53
90.589	9	5.12	0.017	0.051	10.2	0.019	✓	✓	~	–	✓	–	–	0.472–0.984	■	□	□	★★★	★★☆	52
90.590	10	5.12	0.018	0.054	9.7	0.020	✓	✓	~	–	✓	–	–	0.591–1.181	■	□	□	★★★	★★☆	52
90.591	11	5.12	0.019	0.057	9.1	0.022	✓	✓	~	–	✓	–	–	0.709–1.575	■	□	□	★★★	★★☆	46
90.592	12	5.12	0.02	0.061	8.9	0.024	✓	✓	~	–	✓	–	–	0.787–1.969	■	□	□	★★★	★★☆	46

Pégas DOUBLE SKIP — Fast cutting without heat build-up, for hardwoods.

The tooth layout, with a wider gap between teeth, prevents the wood from overheating. A fast blade that delivers a clean, fine finish, excellent in hardwoods.

Model / art. no.	Univ. no.	Length [in]	Blade thick. [in]	Blade width [in]	TPI	Kerf [in]	[1] Material type: Hardwoods	Medium-hard woods	Softwoods	Plywood	Corian & plastics	Non-ferrous metals	Ferrous metals	[2] Recomm. material thick. [in]	[3] Cutting radius: Wide	Tight	Very tight	[4] Finish quality: Cut quality	Underside quality	[5] Gauge
90.520	2/0	5.12	0.009	0.024	24.9	0.009	✓	~	~	–	~	–	–	0.079–0.315	■	■	■	★★★	★★☆	70
90.521	0	5.12	0.009	0.029	22.9	0.010	✓	~	~	–	~	–	–	0.118–0.394	■	■	■	★★★	★★☆	67
90.522	1	5.12	0.01	0.03	21.6	0.011	✓	~	~	–	~	–	–	0.157–0.394	■	■	■	★★★	★★☆	64
90.523	2	5.12	0.012	0.031	19.3	0.013	✓	~	~	–	~	–	–	0.197–0.472	■	■	■	★★★	★★☆	64
90.524	3	5.12	0.013	0.033	17	0.014	✓	~	~	–	~	–	–	0.315–0.591	■	■	■	★★★	★★☆	60
90.525	4	5.12	0.013	0.037	15.7	0.015	✓	~	~	–	~	–	–	0.315–0.709	■	■	□	★★★	★★☆	56
90.526	5	5.12	0.014	0.04	14.7	0.016	✓	~	~	–	~	–	–	0.394–0.787	■	■	□	★★★	★★☆	55
90.527	6	5.12	0.015	0.044	14.5	0.017	✓	~	~	–	~	–	–	0.472–0.787	■	■	□	★★★	★★☆	53
90.528	7	5.12	0.016	0.049	13	0.018	✓	~	~	–	~	–	–	0.472–0.984	■	■	□	★★★	★★☆	53
90.529	8	5.12	0.017	0.05	11.9	0.019	✓	~	~	–	~	–	–	0.591–1.181	■	□	□	★★★	★★☆	52
90.530	9	5.12	0.017	0.051	11.2	0.019	✓	~	~	–	~	–	–	0.709–1.575	■	□	□	★★★	★★☆	52
90.531	10	5.12	0.018	0.054	10.7	0.020	✓	~	~	–	~	–	–	0.787–1.969	■	□	□	★★★	★★☆	52
90.532	11	5.12	0.019	0.057	9.9	0.021	✓	~	~	–	~	–	–	0.787–2.165	■	□	□	★★★	★★☆	46
90.533	12	5.12	0.02	0.061	9.4	0.022	✓	~	~	–	~	–	–	0.984–2.362	■	□	□	★★★	★★☆	46

Pégas MGT — Probably the best blade on the market.

The Modified Geometry Tooth (MGT) is probably the best blade on the market. Its distinctive tooth geometry makes it extremely high-performing: high feed rates, no tear-out, no heat build-up and a very smooth finish. Its high cutting speed makes it best suited to experienced users.

Model / art. no.	Univ. no.	Length [in]	Blade thick. [in]	Blade width [in]	TPI	Kerf [in]	[1] Material type: Hardwoods	Medium-hard woods	Softwoods	Plywood	Corian & plastics	Non-ferrous metals	Ferrous metals	[2] Recomm. material thick. [in]	[3] Cutting radius: Wide	Tight	Very tight	[4] Finish quality: Cut quality	Underside quality	[5] Gauge
90.438	2/0R	5.12	0.009	0.024	15.5	0.010	✓	✓	✓	~	–	–	–	0.197–0.394	■	■	■	★★★	★★★	70
90.439	1R	5.12	0.01	0.03	13.7	0.011	✓	✓	✓	~	–	–	–	0.217–0.591	■	■	■	★★★	★★★	67
90.440	3R	5.12	0.013	0.033	12.4	0.014	✓	✓	✓	~	–	–	–	0.236–0.787	■	■	■	★★★	★★★	60
90.441	5R	5.12	0.014	0.04	11.2	0.016	✓	✓	✓	~	–	–	–	0.256–0.984	■	■	□	★★★	★★★	55
90.442	7R	5.12	0.016	0.049	10.4	0.018	✓	✓	✓	~	–	–	–	0.276–1.181	■	■	□	★★★	★★★	53
90.443	9R	5.12	0.017	0.051	9.7	0.020	✓	✓	✓	~	–	–	–	0.295–1.378	■	□	□	★★★	★★★	52
90.444	12R	5.12	0.02	0.061	8.6	0.024	✓	✓	✓	~	–	–	–	0.335–1.575	■	□	□	★★★	★★★	46

Pégas SKIP REVERSE — A clean underside, with no splintering.

The same tooth geometry as the Skip, but with a set of reversed teeth at the bottom of the blade. Reverse blades prevent the wood from splintering on the underside of the piece. Excellent in softwoods and plywood.

STANDARD

90.426	2/0R	5.12	0.009	0.024	22.1	0.010	~	~	✓	✓	~	–	–	0.118–0.236	■	■	■	★★★	★★★	70
90.427	1R	5.12	0.01	0.03	18.8	0.011	~	~	✓	✓	~	–	–	0.138–0.315	■	■	■	★★★	★★★	67
90.428	3R	5.12	0.013	0.033	16.5	0.014	~	~	✓	✓	~	–	–	0.157–0.394	■	■	■	★★★	★★★	60
90.429	5R	5.12	0.014	0.04	14.5	0.016	~	~	✓	✓	~	–	–	0.197–0.591	■	■	■	★★★	★★★	55
90.430	7R	5.12	0.016	0.049	13	0.018	~	~	✓	✓	~	–	–	0.217–0.787	■	■	□	★★★	★★★	53
90.431	9R	5.12	0.017	0.051	11.9	0.020	~	~	✓	✓	~	–	–	0.236–0.984	■	■	□	★★★	★★★	52

PINNED

90.493	14TPI	5.00	0.01	0.079	14	0.014	–	~	✓	✓	–	–	–	0.217–0.984	■	□	□	★★☆	★★☆	12

Pégas DOUBLE SKIP REVERSE — A clean finish, free of splinters and heat build-…

Like the Double Skip, but in a Reverse version for a tear-free finish on the underside. This blade combines the benefits of the double tooth and the reverse tooth, ideal in woods where heat build-up must be avoided.

90.432	5R	5.12	0.014	0.04	12.2	0.016	~	✓	✓	~	–	–	–	0.315–0.591	■	■	□	★★★	★★★	55
90.433	7R	5.12	0.016	0.049	10.9	0.018	~	✓	✓	~	–	–	–	0.394–0.787	■	■	□	★★★	★★★	53
90.434	9R	5.12	0.017	0.051	9.7	0.020	~	✓	✓	~	–	–	–	0.472–0.984	■	■	□	★★★	★★★	52

Pégas SUPER-HOOK — A miniature band saw for solid hardwoods.

The Super-Hook was created for the demands of solid-hardwood furniture making. A true miniature band saw, it takes 70 mm-thick beech in its stride.

Model / art. no.	Univ. no.	Length [in]	Blade thick. [in]	Blade width [in]	TPI	Kerf [in]	[1] Material type: Hardwoods	Medium-hard woods	Softwoods	Plywood	Corian & plastics	Non-ferrous metals	Ferrous metals	[2] Recomm. material thick. [in]	[3] Cutting radius: Wide	Tight	Very tight	[4] Finish quality: Cut quality	Underside quality	[5] Gauge
90.611	11	5.12	0.02	0.071	8.9	0.025	✓	✓	~	–	–	–	–	0.315–1.575	■	□	□	★★★	★★☆	49
90.612	12	5.12	0.02	0.079	8.4	0.026	✓	✓	~	–	–	–	–	0.354–1.969	■	□	□	★★★	★★☆	46
90.614	14	5.12	0.02	0.094	7.1	0.030	✓	✓	~	–	–	–	–	0.394–1.969	■	□	□	★★☆	★★☆	39
90.616	16	5.12	0.02	0.118	6.6	0.031	✓	✓	~	–	–	–	–	0.433–1.969	■	□	□	★☆☆	★★☆	31
90.618	18	5.12	0.02	0.118	6.1	0.032	✓	✓	~	–	–	–	–	0.472–1.969	■	□	□	★☆☆	★★☆	31
90.624	14	6.30	0.02	0.094	7.1	0.030	✓	✓	~	–	–	–	–	0.394–2.362	■	□	□	★★☆	★★☆	39
90.626	16	6.30	0.02	0.118	6.6	0.031	✓	✓	~	–	–	–	–	0.433–2.953	■	□	□	★☆☆	★★☆	31
90.628	18	6.30	0.02	0.118	6.1	0.032	✓	✓	~	–	–	–	–	0.472–2.953	■	□	□	★☆☆	★★☆	31

Pégas SPIRAL — 360° cutting, without ever turning the workpiece.

Its 360° tooth pattern cuts in every direction without turning the workpiece, allowing very tight angles. It also handles long pieces that could not be turned on a conventional scroll saw. Highly effective in many materials, it leaves a coarser finish.

Model / art. no.	Univ. no.	Length [in]	Blade thick. [in]	Blade width [in]	TPI	Kerf [in]	[1] Material type: Hardwoods	Medium-hard woods	Softwoods	Plywood	Corian & plastics	Non-ferrous metals	Ferrous metals	[2] Recomm. material thick. [in]	[3] Cutting radius: Wide	Tight	Very tight	[4] Finish quality: Cut quality	Underside quality	[5] Gauge
90.500	2/0	5.12	0.024	–	59.2	0.028	–	~	✓	~	–	–	–	0.079–0.197	■	■	■	★☆☆	★☆☆	67
90.501	0	5.12	0.029	–	54.1	0.034	–	~	✓	~	–	–	–	0.118–0.236	■	■	■	★☆☆	★☆☆	64
90.502	1	5.12	0.03	–	50.8	0.035	–	~	✓	~	–	–	–	0.157–0.276	■	■	■	★☆☆	★☆☆	60
90.503	2	5.12	0.031	–	46.2	0.038	–	~	✓	~	–	–	–	0.197–0.315	■	■	■	★☆☆	★☆☆	56
90.504	3	5.12	0.034	–	42.4	0.041	–	~	✓	~	–	–	–	0.236–0.394	■	■	■	★☆☆	★☆☆	55
90.505	4	5.12	0.037	–	39.1	0.045	–	~	✓	~	–	–	–	0.276–0.472	■	■	■	★☆☆	★☆☆	55
90.506	5	5.12	0.04	–	36.3	0.048	–	~	✓	~	–	–	–	0.315–0.551	■	■	■	★☆☆	★☆☆	53
90.507	6	5.12	0.044	–	33.8	0.052	–	~	✓	~	–	–	–	0.354–0.63	■	■	■	★☆☆	★☆☆	53
90.508	7	5.12	0.049	–	31.8	0.057	–	~	✓	~	–	–	–	0.394–0.709	■	■	■	★☆☆	★☆☆	52
90.509	8	5.12	0.05	–	29	0.058	–	~	✓	~	–	–	–	0.472–0.787	■	■	■	★☆☆	★☆☆	46

Pégas METAL CUTTING — The specialist for ferrous and non-ferrous metals.

Its specific tooth geometry and heat treatment make this blade highly effective in ferrous and non-ferrous metals. It delivers fine, precise cuts and can also be used by hand.

Model / art. no.	Univ. no.	Length [in]	Blade thick. [in]	Blade width [in]	TPI	Kerf [in]	[1] Material type: Hardwoods	Medium-hard woods	Softwoods	Plywood	Corian & plastics	Non-ferrous metals	Ferrous metals	[2] Recomm. material thick. [in]	[3] Cutting radius: Wide	Tight	Very tight	[4] Finish quality: Cut quality	Underside quality	[5] Gauge
90.540	3/0	5.12	0.009	0.019	59.7	0.010	–	–	–	~	~	✓	✓	0.039–0.177	■	■	■	★★☆	★★☆	70
90.541	2/0	5.12	0.01	0.02	55.9	0.011	–	–	–	~	~	✓	✓	0.043–0.197	■	■	■	★★☆	★★☆	70
90.542	0	5.12	0.011	0.023	52.1	0.012	–	–	–	~	~	✓	✓	0.047–0.197	■	■	■	★★☆	★★☆	70
90.543	1	5.12	0.012	0.025	48.3	0.013	–	–	–	~	~	✓	✓	0.051–0.217	■	■	■	★★☆	★★☆	70
90.544	2	5.12	0.013	0.028	44.4	0.014	–	–	–	~	~	✓	✓	0.059–0.236	■	■	■	★★☆	★★☆	67
90.545	3	5.12	0.014	0.029	40.6	0.015	–	–	–	~	~	✓	✓	0.063–0.256	■	■	■	★★☆	★★☆	67
90.546	4	5.12	0.015	0.031	38.1	0.016	–	–	–	~	~	✓	✓	0.067–0.276	■	■	□	★★☆	★★☆	64
90.547	5	5.12	0.016	0.033	35.6	0.017	–	–	–	~	~	✓	✓	0.071–0.315	■	■	□	★★☆	★★☆	60
90.548	6	5.12	0.017	0.037	34.3	0.017	–	–	–	~	~	✓	✓	0.079–0.354	■	■	□	★★☆	★★☆	60
90.549	8	5.12	0.02	0.045	27.9	0.020	–	–	–	~	~	✓	✓	0.087–0.394	■	■	□	★★☆	★★☆	55

Pégas REGULAR — The rugged all-purpose blade for a wide range of work.

Pinned version of the Regular, identical to the 5" and 6" Regular blades but fitted with pins, for saws that take pin-end blades. The 6.5" Coping can also be used by hand with a frame.

Model / art. no.	Univ. no.	Length [in]	Blade thick. [in]	Blade width [in]	TPI	Kerf [in]	[1] Material type: Hardwoods	Medium-hard woods	Softwoods	Plywood	Corian & plastics	Non-ferrous metals	Ferrous metals	[2] Recomm. material thick. [in]	[3] Cutting radius: Wide	Tight	Very tight	[4] Finish quality: Cut quality	Underside quality	[5] Gauge
STANDARD																				
90.462	20TPI	5.12	0.02	0.118	20	0.028	~	~	~	~	✓	~	–	0.157–1.181	■			★★☆	★★☆	30
90.464	15TPI	5.12	0.02	0.118	15	0.028	~	~	~	~	✓	~	–	0.197–1.378	■			★★☆	★★☆	30
90.465	10TPI	5.12	0.02	0.118	10	0.028	~	~	~	~	✓	~	–	0.295–1.969	■			★★☆	★★☆	30
90.470	20TPI	5.98	0.02	0.118	20	0.028	~	~	~	~	✓	~	–	0.157–1.181	■			★★☆	★★☆	30
90.471	15TPI	5.98	0.02	0.118	15	0.028	~	~	~	~	✓	~	–	0.197–1.378	■			★★☆	★★☆	30
90.472	10TPI	5.98	0.02	0.118	10	0.028	~	~	~	~	✓	~	–	0.295–1.969	■			★★☆	★★☆	30
NARROW BLADE																				
90.460	25TPI	5.12	0.02	0.071	25	0.027	~	~	~	~	✓	~	–	0.118–0.787	■			★★☆	★★☆	46
90.461	20TPI	5.12	0.02	0.071	20	0.028	~	~	~	~	✓	~	–	0.157–0.984	■			★★☆	★★☆	46
PINNED																				
90.475	20TPI	5.00	0.02	0.118	20.1	0.028	~	~	~	~	✓	~	–	0.138–1.181	■			★★☆	★★☆	12
90.476	15TPI	5.00	0.02	0.118	15	0.028	~	~	~	~	✓	~	–	0.197–1.378	■			★★☆	★★☆	12
90.477	10TPI	5.00	0.02	0.118	10.2	0.028	~	~	~	~	✓	~	–	0.295–1.969	■			★★☆	★★☆	12
90.478	25TPI	5.00	0.01	0.079	25.4	0.016	~	~	~	~	✓	~	–	0.118–0.787	■			★★☆	★★☆	12
90.487	25TPI	2.95	0.01	0.079	25.4	0.016	~	~	~	~	✓	~	–	0.118–0.787	■	■		★★☆	★★☆	12
PINNED · COPING																				
90.552	20TPI	6.50	0.02	0.118	20	0.028	✓	~	~	~	~	–	–	0.157–1.181	■			★★☆	★★☆	12
90.551	18TPI	6.50	0.02	0.094	18	0.028	✓	~	~	~	~	–	–	0.157–1.378	■			★★☆	★★☆	12
90.553	15TPI	6.50	0.02	0.118	15	0.028	✓	~	~	~	~	–	–	0.197–1.378	■			★★☆	★★☆	12
90.554	10TPI	6.50	0.02	0.118	10	0.028	✓	~	~	~	~	–	–	0.295–1.969	■			★★☆	★★☆	12

Pégas HOOK · pinned — Fast cut-offs in thick stock.

A special coarse-tooth pinned blade for cutting thick stock. It works like a miniature band saw.

Model / art. no.	Univ. no.	Length [in]	Blade thick. [in]	Blade width [in]	TPI	Kerf [in]	[1] Material type: Hardwoods	Medium-hard woods	Softwoods	Plywood	Corian & plastics	Non-ferrous metals	Ferrous metals	[2] Recomm. material thick. [in]	[3] Cutting radius: Wide	Tight	Very tight	[4] Finish quality: Cut quality	Underside quality	[5] Gauge
90.485	7TPI	5.00	0.02	0.118	7.1	0.029	✓	✓	~	–	–	–	–	0.394–1.969	■			★★☆	★★☆	12

Pégas SKIP PROGRESSIVE — A gentle start, ideal for beginners.

The "Progressive" blades were designed for hand use. Their progressive tooth pattern, active at the start and end of the cutting section, makes them especially resistant to breakage. Entry into the material is very gentle and jolt-free, which makes them particularly suited to children, students and beginners.

Model / art. no.	Univ. no.	Length [in]	Blade thick. [in]	Blade width [in]	TPI	Kerf [in]	[1] Material type: Hardwoods	Medium-hard woods	Softwoods	Plywood	Corian & plastics	Non-ferrous metals	Ferrous metals	[2] Recomm. material thick. [in]	[3] Cutting radius: Wide	Tight	Very tight	[4] Finish quality: Cut quality	Underside quality	[5] Gauge
90.403	2	5.12	0.0118	0.0307	21	0.013	✓	✓	✓	✓	–	–	–	0.118–0.394	■	■	■	★★☆	★★☆	64
90.406	5	5.12	0.0142	0.0402	17	0.016	✓	✓	✓	✓	–	–	–	0.315–0.591	■	■		★★☆	★★☆	55
90.409	8	5.12	0.0165	0.0504	14	0.019	✓	✓	✓	✓	–	–	–	0.472–0.787	■			★★☆	★★☆	53

Pégas REGULAR PROGRESSIVE — The progressive blade for metals and hard …

A blade based on the same principles as the Skip Progressive, but aimed more specifically at cutting metals and materials harder than wood. Its progressive tooth pattern ensures a gentle entry and good resistance to breakage.

Model / art. no.	Univ. no.	Length [in]	Blade thick. [in]	Blade width [in]	TPI	Kerf [in]	[1] Material type: Hardwoods	Medium-hard woods	Softwoods	Plywood	Corian & plastics	Non-ferrous metals	Ferrous metals	[2] Recomm. material thick. [in]	[3] Cutting radius: Wide	Tight	Very tight	[4] Finish quality: Cut quality	Underside quality	[5] Gauge
90.466	2/0	5.12	0.009	0.024	45.7	0.011	–	–	~	~	✓	✓	✓	0.059–0.197	■	■	■	★★☆	★★☆	70
90.467	2	5.12	0.012	0.031	39.4	0.014	–	–	~	~	✓	✓	✓	0.079–0.315	■	■	■	★★☆	★★☆	67
90.468	5	5.12	0.014	0.04	30	0.017	–	–	~	~	✓	✓	✓	0.098–0.472	■	■	□	★★☆	★★☆	60
90.469	8	5.12	0.017	0.05	24.1	0.020	–	–	~	~	✓	✓	✓	0.118–0.787	■	■	□	★★☆	★★☆	55

Pégas DOVETAIL — To date, the only blade for hand-bow dovetails.

To date, the only scroll-saw blade developed for cutting dovetails and fine joinery in hardwood using a hand bow. Its teeth all point toward the centre of the blade, for a clean entry on both sides of the workpiece.

90.650	5	5.12	0.013	0.043	16.5	0.016	✓	✓	✓	–	–	–	–	0.118–0.394	■	■	□	★★★	★★★	55
90.651	9	5.12	0.017	0.055	13.2	0.019	✓	✓	✓	–	–	–	–	0.394–0.984	■	■	□	★★★	★★★	52